

TRADESMAN MANUFACTURING
IS PLEASED TO ANNOUNCE

A NEW LINE OF E-Z SEAL FITTINGS



SPECIFICATIONS

E-Z SEAL fittings are manufactured from galvanized steel, meeting spec ASTM A-653 (Lockforming quality). They feature a double legged EPDM gasket which creates a virtually airtight connection when slipped into spiral pipe. The gasket is mechanically attached to the fitting with a 180 degree hemmed edge. This hem gives added rigidity to the fittings, ensures that the gasket will never slip out of place and makes a safe rounded edge for the installer.

E-Z SEAL has been pressure tested and meets the requirements of SMACNA Leakage Class 3 for -2" w.g. to +10" w.g. (test data available upon request). E-Z Seal gasket has an operating temperature of -40 degrees to +250 degrees Fahrenheit. The smoke and flame spread is 0/0 in compliance with ASTM E-84-91A.

E-Z SEAL fittings are designed to slip snugly into your spiral pipe. Simply insert the fitting to the spiral stop bead and secure with self tapping sheet metal screws. Screws must be placed within one inch of the spiral stop bead and at uniform intervals not to exceed 15" along the circumference. A minimum of three screws must be used on all diameters 14" or less.

4437 - 8th Avenue North
Lethbridge, Alberta
T1H 6W5

P 403-327-9871
Toll Free P 888-281-8040
F 403-329-9079

TM TRADESMAN
MANUFACTURING